






## PROTECTIVE RELAY 保護繼電器

SPECIFICATION 規格	H2Q-N	H2Q-Y	PU-NC
Model 型號			
Dimension(mm) 尺寸	61H*49W*70D	88H*58W*68D	50H*40W*57.5D
Functions 功能特性	<ul style="list-style-type: none"> <li>&gt; With 2C (D.P.D.T) contact, it can choose positive edge trigger (power on) or negative edge trigger (power off) operation.</li> <li>&gt; Contact can keep on after power off, and contact can revolve when next signal trigger.</li> <li>&gt; 具有2C接點，可選擇正緣(通電)或負緣(斷電)動作。</li> <li>&gt; 斷電後接點可保持，當下一次訊號來時接點才可以轉換。</li> </ul>		<ul style="list-style-type: none"> <li>&gt; Power supply for proximity and photoelectric switches</li> <li>&gt; Without change DIP switch can use for PNP or NPN type proximity switches</li> <li>&gt; With DCV stabilizing device.</li> <li>&gt; 近接光電開關用電源供給控制器</li> <li>&gt; 不需切換開關可用於電壓型(P型)及電流型(N型)</li> <li>&gt; 輸出電源具有隱壓裝置</li> </ul>
Supply Voltage 額定電壓	AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz		
Contact Rating 接點容量	250VAC 5A Resistive Load 48VDC 5A 電阻性負載		
Reset Time 複歸時間	0.3 sec max		0.1 sec max
Consumed Power 消耗功率	2VA		
Ambient Temperature 使用周圍溫度	-10°C~+55°C		
Ambient Humidity 使用周圍濕度	45~85%RH		
Life 壽命	Mechanical 機械	5×10 <sup>6</sup> times	
	Electrical 電氣	10 <sup>5</sup> times	
Weight 重量	170g		
Connection 接線圖	<p>H2Q 限時1C</p> 		<p>PU-NC 輸出接點:1C</p> 
Timing Chart 時序圖	