

## FLOATLESS RELAY 液面控制器

SPECIFICATION 規格		AFR-1	C61F-GP
Model 型號			
Dimension(mm) 尺寸		61H*49W*70D	50H*40W*57.5D
Supply Voltage 額定電壓		AC(V): 110, 220, 240, 50/60Hz	
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載	
Operating Voltage 動作電壓		85 ~ 110% of Rated Voltage 額定電壓值的 85 ~ 110%	
Second Voltage 電極內電壓		8VAC (except HIGH SENSING 24VAC)	
Operate Resistance 動作電阻		4KΩ min. (GENERAL)	
Release Resistance 釋放電阻		15KΩ min. (GENERAL)	
Response Time 反應時間		Operate: 80 msec max. Release: 160msec max. 動作: 80 msec 以下 釋放: 160msec 以下	
Length Of Cable 電纜長度		1Km max. (GENERAL)	
Insulation Resistance 絕緣電阻		100Ω (DC 500V) min.	
Dielectric Strength 耐電壓		1500VAC, 50/60Hz, for 1 min.	
Consumed Power 消耗功率		3.2VA	
Ambient Temperature 使用周圍溫度		-10°C ~ +55°C	
Ambient Humidity 使用周圍濕度		45~85%RH	
Life 壽命	Mechanical 機械	5×10 <sup>6</sup> times min	
	Electrical 電氣	10 <sup>5</sup> times min	
Weight 重量		200g	160g
Connection 接線圖		<p>General Water-Supply Running 一般自動給水裝置</p> 	<p>General Drainage Running 一般排水裝置</p> 